

TILE ADHESIVE

Mychem provides one of the most comprehensive sets of solutions dedicated to tile setting for both residential and commercial buildings. It is always crucial to select the right tile and the right tile installation system for each different area of the specific project.



MYFIX - BASIC

CEMENTITIOUS WATERPROOFING COATING
 • BOND WELL TO HEAVY TOPPING
 • CAN DIRECT CONTACT WITH WATER

MYFIX BASIC is a general use premixed cementitious tile adhesive for bonding of various type ceramic tiles. It is suitable for fixing ceramic glazed tiles for both floor and wall for internal applications. The product can enhance for the external application if mix with MyMix 358.

USES FOR
 Ceramic tiles, natural stones, monocottura, slate, quarry tiles, and terracotta.

Performance Properties	
Appearance	Grade
Flowability	High
Wet Grout, 30°C	20-25
Wet Grout, 20°C	20-25
Adhesion to Substrate	1.5
Adhesion to Substrate	1.5
Adhesion to Substrate	1.5
Setting Time, Hours	24

PACKAGING
 25kg & 20kg Paper bag



MYFIX - STANDARD

STANDARD CEMENT BASED ADHESIVE
 • SUITABLE FOR CERAMIC TILE AND STONE APPLICATIONS
 • FOR THICK AND THIN APPLICATION
 • NON TOXIC

MYFIX STANDARD is a general use premixed cementitious tile adhesive for bonding of various type ceramic tiles. It is suitable for fixing ceramic glazed tiles for both floor and wall for internal applications. The product can enhance for the external application if mix with MyMix 358.

USES FOR
 Ceramic tiles, natural stones, monocottura, slate, quarry tiles, and terracotta.

Performance Properties	
Appearance	Grade
Flowability	High
Wet Grout, 30°C	20-25
Wet Grout, 20°C	20-25
Adhesion to Substrate	1.5
Adhesion to Substrate	1.5
Adhesion to Substrate	1.5
Setting Time, Hours	24

PACKAGING
 25kg Paper bag



MYFIX - SUPER

IMPROVED CEMENT BASED ADHESIVE
 • HIGH BOND STRENGTH
 • NON TOXIC
 • SUITABLE FOR TILE AND STONE APPLICATIONS

MYFIX SUPER is a High strength premixed cementitious tile adhesive with extended open time for longer application especially for big tiles. It is suitable for various type of tiles for either interior or exterior with no vertical slip.

USES FOR
 Ceramic tiles, natural stones, monocottura, slate, quarry tiles, and terracotta.

Performance Properties	
Appearance	Grade
Flowability	High
Wet Grout, 30°C	20-25
Wet Grout, 20°C	20-25
Adhesion to Substrate	1.5
Adhesion to Substrate	1.5
Adhesion to Substrate	1.5
Setting Time, Hours	24

PACKAGING
 25kg Paper bag



MyHIJAU Mark Product

Ceramic Tile Adhesive

MYCHEM Industries Sdn. Bhd.

MyHP00165/25



General Information

A1. Product Classification

Category	PG-02 Paint & Coating
Sub-category	PG-02 A Paint & Coating

A2. General Product Information

Product Name	Ceramic Tile Adhesive
Brand	MYCHEM
Model	MyFix Super
Special feature	-

A3. Manufacturer / Seller Information

Ownership

Manufacturer

Manufacturer name	MYCHEM Industries Sdn. Bhd.
Country of manufacturing	-
Manufacturer sales office	-
Manufacturer website	-
Contact person phone	-
Contact person's email	-
Distributor/Trader	
Distributor/Trader name	-
Manufacturer name	-
Country of manufacturing	-
Distributor sales office address	-
Distributor/Trader website	-
Contact person phone	-
Contact person's email	-
Made in Malaysia	-
Bumiputera	-
Registered with e-perolehan	-

A4. Recommended Retail Price (RRP)

Recommended retail price (RRP)	-
--------------------------------	---

Environment Specification

B1. Materials Selection

Sustainable management certified material -

B2. Hazardous Substance Content

Hazardous content complies with environmental standard. -

Product Certifications & Standards

C1. MyHIJAU Mark

Listing Number MyHP00165/25

Certified Date 11-04-2025

Expiry Date 24-03-2027

Compliance Category -

Certificate Scheme -

Verification Body -

Issuing Country -

Environmental Claims -

C2. Additional Green Product Certification (as per GGP Guideline 3.0)

Additional Green Product Certification (as per GGP Guideline 3.0) -

C3. Others Compliance with Government Requirement

Others Compliance with Government Requirement -

C4. Environmental Management System

Environmental Management System -

C5. Energy Management System

Energy Management System -

Get Product

Contact Person

Company Name MYCHEM Industries Sdn. Bhd.

Primary Contact Person

Contact Person's Name Mr. Jaycee

Contact Person's Designation Operation Director

Contact Person's Phone Number 124355631

Contact Person's Email jaycee@mychem.com.my

Secondary Contact Person

Contact Person's Name Mr. Kyson Yap

Contact Person's Designation Production Manager

Contact Person's Phone Number 168786522

Contact Person's Email kyson@mychem.com.my

Company Address

Address	Lot 27219, Lorong Haji Abdul Manan 2, Batu 5, Jalan Meru, 42200 Klang
City	Klang
Postcode	42200
State	Selangor
Country	Malaysia
Phone Number	124355631
Fax Number	none